


FULLY COATED TIES

STFC(Stainless Steel Fully Coated) TYPE



DONG-A STFC Type Cable Ties provide excellent resistance to chemical, salt-spray and to prevent cable damage. Also it provides additional insulation between tie and bundle materials.



Material : Fire, UV, weather and corrosion resistant

- AISI 304 Stainless Steel for most applications.
- AISI 316(or 316L) Stainless Steel for requiring superior corrosion resistance.
- Coating Material : PVC, Epoxy Resin, Nylon(Fig.2)

PART NO			BUNDLE DIA mm(inch)	LENGTH mm(inch) "L"	WIDTH mm(inch) "W"	TENSILE kg (LBS)	Pkg Qty
304	316	GS ^(*)					
STFC 125-304	STFC 125-316	GTFC 125	35(1.37)	125(4.9)	4.6 (.18)	45.4 (100)	100
STFC 150-304	STFC 150-316	GTFC 150	44(1.70)	150(6.0)			
STFC 200-304	STFC 200-316	GTFC 200	50(2.00)	200(8.0)			
STFC 360-304	STFC 360-316	GTFC 360	102(4.00)	360(14.2)			
STFC 520-304	STFC 520-316	GTFC 520	152(6.00)	520(20.4)			
STFC 680-304	STFC 680-316	GTFC 680	203(8.00)	680(26.8)			
STFC 840-304	STFC 840-316	GTFC 840	254(10.0)	840(33.0)			
STFC 1000-304	STFC 1000-316	GTFC 1000	318(12.50)	1050(41.3)	7.9 (.31)	113.4 (250)	50
STFC 150HD-304	STFC 150HD-316	GTFC 150HD	44(1.70)	150(6.0)			
STFC 200HD-304	STFC 200HD-316	GTFC 200HD	50(2.00)	200(8.0)			
STFC 360HD-304	STFC 360HD-316	GTFC 360HD	102(4.00)	360(14.2)			
STFC 520HD-304	STFC 520HD-316	GTFC 520HD	152(6.00)	520(20.4)			
STFC 680HD-304	STFC 680HD-316	GTFC 680HD	203(8.00)	680(26.8)			
STFC 840HD-304	STFC 840HD-316	GTFC 840HD	254(10.0)	840(33.0)			
STFC 1000HD-304	STFC 1000HD-316	GTFC 1000HD	318(12.50)	1050(41.3)	13.0 (.51)	227.0 (500)	50
STFC 200EHD-304	STFC 200EHD-316	GTFC 200EHD	50(2.00)	200(8.0)			
STFC 360EHD-304	STFC 360EHD-316	GTFC 360EHD	102(4.00)	360(14.2)			
STFC 520EHD-304	STFC 520EHD-316	GTFC 520EHD	152(6.00)	520(20.4)			
STFC 680EHD-304	STFC 680EHD-316	GTFC 680EHD	203(8.00)	680(26.8)			
STFC 840EHD-304	STFC 840EHD-316	GTFC 840EHD	254(10.0)	840(33.0)			
STFC 1000EHD-304	STFC 1000EHD-316	GTFC 1000EHD	318(12.50)	1050(41.3)			
STFC 200EXD-304	STFC 200EXD-316	GTFC 200EXD	50(2.00)	200(8.0)	16.0 (5/8")	227.0 (500)	50
STFC 360EXD-304	STFC 360EXD-316	GTFC 360EXD	102(4.00)	360(14.2)			
STFC 520EXD-304	STFC 520EXD-316	GTFC 520EXD	152(6.00)	520(20.4)			
STFC 680EXD-304	STFC 680EXD-316	GTFC 680EXD	203(8.00)	680(26.8)			
STFC 840EXD-304	STFC 840EXD-316	GTFC 840EXD	254(10.0)	840(33.0)			
STFC 1000EXD-304	STFC 1000EXD-316	GTFC 1000EXD	318(12.50)	1050(41.3)			
STFC 200PD-304	STFC 200PD-316	GTFC 200PD	50(2.00)	200(8.0)			
STFC 360PD-304	STFC 360PD-316	GTFC 360PD	102(4.00)	360(14.2)			
STFC 520PD-304	STFC 520PD-316	GTFC 520PD	152(6.00)	520(20.4)			
STFC 680PD-304	STFC 680PD-316	GTFC 680PD	203(8.00)	680(26.8)			
STFC 840PD-304	STFC 840PD-316	GTFC 840PD	254(10.0)	840(33.0)			
STFC 1000PD-304	STFC 1000PD-316	GTFC 1000PD	318(12.50)	1050(41.3)			

■ HAND TOOL : See Page C8

(*) GS means Galvanized cold rolled steel according to International Standard(ASTM A366-91 or Equivalent)
GTFC : Quality Approvals - ABS, LR, DNV

QUALITY APPROVALS



Lloyd's Register
of Shipping



Det Norske Veritas



TYPE APPROVAL PROGRAM
American Bureau
of Shipping



BUREAU VERITAS
Bureau Veritas



RMRS
Russian Maritime
Register of Shipping.



GOST
GOSTSTANDART