

## Liquid - Tight Flexible Metal Conduit - EF - Interlocked

### The Product - Standard grade liquid - tight flexible conduit

- Galvanized steel strip, interlocked.
- Water - proof.
- High flexibility suitable to a wide range of application.
- PVC jacket in grey and black color.

### Application

Seals Out abrasives, alcohol, fumes, gases, dirt, oils, water and spray suitable for the following potentials :

- Machine tools
- Silo and plant
- High rise buildings
- Air conditioning and ventilation
- Computer
- Security



Nominal Size	Diameter				Length without Coupling		Min. Bending Radius	Length of Each Roll	
	Inside Diameter		Outside Diameter						
	min. mn.	max. mm.	min. mn.	max. mm.	min. mn.	max. mm.	mm.	ft.	m.
1/2"	15.70	16.30	20.80	21.30	1.00	1.35	70	200	60
3/4"	20.70	21.30	26.20	26.70	1.10	1.55	100	100	30
1"	26.20	26.90	32.70	33.40	1.70	1.95	150	100	30
1-1/4"	35.10	35.70	41.50	42.20	1.25	1.70	180	50	15
1-1/2"	40.20	40.80	47.40	48.30	1.80	2.30	250	50	15
2"	51.00	51.80	59.40	60.30	2.40	2.80	430	50	15
2-1/2"	62.50	64.00	72.10	73.00	2.00	2.50	550	25	7.5
3"	77.60	78.80	87.70	88.90	2.50	3.20	800	25	7.5
4"	101.10	102.50	113.20	114.30	2.80	3.03	1200	25	7.5

The above data might be changed without prior notice.  
Special sizes are available on request